



FOUNDATION ENCLOSURE (WHEN PROVIDED) SHALL HAVE 1 SQUARE FOOT NET VENT AREA PER 1/150th OF THE FLOOR AREA, AND AN 18"x24" MINIMUM CRAWL SPACE ACCESS, SITE INSTALLED BY OTHERS SUBJECT TO LOCAL JURISDICTION.



HANDICAP RAMP, STAIRS, AND HANDRAILS
SITE INSTALLED, DESIGNED BY OTHERS, AND
SUBJECT TO LOCAL CODE INSPECTION.



SEE CROSS SECTION FOR
ROOF VENTILATION METHOD

TEXAS INDUSTRIALIZED BUILDING CODE COUNCIL
This document is approved pursuant to
the Industrialized Housing and Buildings Act.
DRA No. 17 IBC ✓ IRC _____
Date: Dec 13, 2013
DRA Signature: *[Signature]*

THIRD PARTY:

RADCO
5801 BENJAMIN CENTER DRIVE #102
TAMPA, FLORIDA 33634
PH: (813) 243-0370



KENNETH EARL DUNMON
PROFESSIONAL ENGINEER
AMERICUS, GEORGIA

Manufacture:


KINGS CUSTOM BUILDERS, INC
1608 US HIGHWAY 19S
ELLAVILLE, GA 31806
PH: 229-937-2538
FX: 229-937-2150

Dealer:

ROSE OFFICE SYSTEMS

Project:

KINSEL FORD

SERIAL# K01111335383 AB			
SALESPERSON: MATTHEW TAYLOR	DRAWN BY: CHRISTIE WHITE	MODEL#: 28X62	APPROVAL:
CODE: TX1BC	LABEL: TX16ABCD	Sheet:	
Date: 11.24.13	OCCUPANCY: BUSINESS		
Scale: 1/4" = 1'-0"	QUOTE#: MT2716 R1		

FRAME & FLOOR			WALLS--WINDOWS--DOORS			8'-0"		EXTERIOR		ROOF		ELECTRICAL		SINGLE		PHASE		A/C & HEAT		RESTROOMS							
AXLES	BRAKE	(6) EACH NEW	PLATES	DOUBLE TOP	2"x4"	BOTTOM	2"x4"	OVER HOUSE WRAP OVER 7/16" OSB		ROOF DRAINS W/ EXTERNAL DOWNSPOUTS		ENTRANCE PANEL		(2) 150		AMP		TYPE A/C (2) 3TON WALL MT BARD		STANDARD		HANDICAP		2		1/2	
HITCH			REMOVABLE			XXXX			STANDARD			STYLE		TRANSVERSE		LIGHTS (16)4FT 4 BULB SURFACE MT. DIFFUSED FLOURESCENT		(2) 4FT 2 BULB SURFACE MT. DIFFUSED FLOURESCENT		PROGRAMMABLE THERMOSTATS		COMMODE(S)		(1) H/C TANK TYPE		(1) RIGHT HAND H/C TANK TYPE	
I-BEAM			12"			INSULATION R--			EXTERIOR: 13K INTERIOR: 11UF			CORNERS		PLEKO CORNER BLOCKS (QUOINS)		CEILING JOIST: 2"x4"x161" @ 16" O.C.		LIGHTS (1) CEILING MT DOME LIGHT		W.H. LAV		(2) W/CHROME WRIST BLADE FAUCET					
JOIST			OUTRIGGER FRAME W/ 95 1/2" BRAKE AXLES			COVERING			5/8" TYPE-X VINYL COVER GYP (SOFT WHITE)			BOTTOM TRIM		SHIP 6" HARDI TRIM LOOSE		16" OVERHANG ON END WALLS/2" ON SIDEWALLS		(1)13WATT FLOURESCENT PORCH LIGHT W/PHOTOCELL		TYPE HEAT		10KW EACH		MIRROR		N/A	
			2"x6"x161" @ 16" O.C.			CUT BACK:			INTERIOR: 12"--20"			SHIP LOOSE 12"x70" BLACK ROOF CAP		36" G-STYLE TYPE MANSARD W/PLEKO TRIM		PLEKO TRIM ON WINDOWS AND DOORS		(2)HPS 70WATT (W/PHOTOCELL) NO SWITCH				GRAB BAR		(2) 36" (2) 42" @ 36" AFF (2) 18" VERTICAL @ 39" AFF			
INSUL R--			19UF									TOP TRIM		PLEKO TRIM IS SW7626 ZURICH WHITE		DECKING		7/16" CLASS C FR DECK		(4)2 BULB WHITE FLOOD LIGHTS(W/PHOTOCELL--NO SWITCH)BULBS BY OTHERS				VANITY		N/A	
																POWER VENTS		(2) BROAN L150 (150 CFM EACH)				URINAL		N/A			
																ENTRANCE CONDUIT		1 1/2" PVC									
DECKING			3/4" T&G PLYWOOD									INSULATION R--		49K		EXIT SIGNS		(2) W/BATTERY BACK UP		SUPPLY AIR SYSTEM		1 1/2" FIBERGLASS		SHOWER		N/A	
COVERING			20oz (30452) SALISBURY ACTION BACK CARPET			4" (502 BROWN) VINYL BASE MOLDING THRU OUT EXCEPT IN R.R.						TIE DOWNS		NO		(2) CEILING MT DIRECTIONAL				RETURN AIR SYSTEM		1 1/2" FIBERGLASS		WATER HEATER		(1) 6 GAL. (ON LAMINATE SHELF ABOVE MOP SINK)	
LVT (CANYON) SUPPLIED BY ROSE INSTALLED BY KINGS IN BATHS,						6" (502 BROWN) VINYL BASE MOLDING IN R.R. ONLY						SKIRTING:		(12) 4X8 CERTAINTeed (STUCCO)		EMERGENCY LIGHTS		(2) XR-5 W/DUAL REMOTE HEAD EACH						SPECIAL			
BREAK, HALLWAY, & LOBBY (RAN WITH LENGTH OF BUILDING)						PREFINISHED VCG MOLDING PACKAGE						(12) 2X2X8' PT LUMBER				(1) STANDARD EMERGENCY LIGHT								(1) ICE MAKER HOOKUP			
CUT BACK:			Finish			N/A (SHIP 4" CARPET BAR LOOSE)			P/G HOUSE TYPE WINDOW MOLDING			(8) VENTS			DECALS		NONE								(1) 24X24 ABS MOP SINK W/LEGS		
			Decking			1" @ ALCOVE						DECALS		NONE		Gypsum		CEILING BEAM @ MATELINE		(1) WALL MT. J--BOX W/ 1/2" EMT STUB THRU FLOOR @ 72" AFF		(2) V--2247 PASSIVE VENTS					

NOTE: ALL WALL DIMENSIONS ARE TO WALL FINISH AND NOT TO THE STUD!!!

ALL INTERIOR WALL AND CEILING FINISHES SHALL BE CLASS B OR BETTER IN CORRIDORS, AND CLASS C OR BETTER IN ROOMS AND ENCLOSED SPACES; CARPET SHALL BE CLASS II OR BETTER.

NOTE: ALL HEIGHTS SPECIFIED A.F.F. (ABOVE FINISHED FLOOR) ARE MEASURED TO THE BOTTOM OF THE OBJECT OR ITEM.

COLOR CHART

- WALLS
- WINDOWS
- DOORS
- ELECTRICAL
- WIRING
- HVAC / DUCT / DIFFUSERS
- DIMENSIONS
- TRUSS BAYS
- PLUMBING

PANEL BOX

DUPLEX RECEPTACLE 120v

PORCH LIGHT

EXT. WEATHERPROOF 120v REC.

DEDICATED RECEPT

VENT FAN

FLUORESCENT LIGHT w/2-32W BULBS

FLUORESCENT LIGHT w/4-32W BULBS

ENGINEERED ORDER TRUSS DESCRIPTION

DIRECTIONAL EXIT SIGN

SINGLE SWITCH

DOUBLE SWITCH

WALL MOUNTED LIGHTED EXIT SIGN W/ BATTERY PACK

XR5 EMERGENCY LIGHT

XR5 EMERGENCY REMOTE HEAD

12"x12" RETURN AIR GRILLE (CEILING)

6"x10" SUPPLY AIR DIFFUSER (CEILING)

THERMOSTAT

ICEMAKER

TX CODES AND LOADS

STRUCTURAL LOAD LIMITATIONS

FLOOR LIVE LOAD:
50 PSF 100 PSF IN CORRIDOR
2000 PSF CONCENTRATED FLOOR LOAD OVER 30x30 INCH AREA LOCATED ANYWHERE ON FLOOR.

ROOF LIVE LOAD:
A. 20 PSF

ROOF SNOW LOAD:
A. Pg = 20 PSF
B. Pf = 20 PSF
C. Ce = 1.1
D. Is = 1.0
E. Ct = 1.0

GROUND SNOW LOAD
ROOF SNOW LOAD
SNOW EXPOSURE FACTOR
SNOW IMPORTANCE FACTOR
SNOW THERMAL FACTOR

WIND LOAD:
A. 130 MPH
B. Iw = 1.0
C. C
D. Gcpl = 0.18
E. Fw

WIND SPEED
WIND IMPORTANCE FACTOR
WIND EXPOSURE CATEGORY
INTERNAL PRESSURE COEFFICIENT
WALL COMPONENT AND CLADDING LOAD

ZONE 1 = 34.6 PSF
ZONE 2 = 55.5 PSF
ZONE 3 = 92.9 PSF

ROOF COMPONENT AND CLADDING LOAD
ZONE 4 = 38.2 PSF
ZONE 5 = 46.0 PSF


G. THIS BUILDING IS NOT DESIGNED FOR PLACEMENT ON THE UPPER HALF OF A HILL OR ESCARPMENT EXCEEDING IN 15 FEET.

SEISMIC LOAD:
A. IE = 1.0
B. D
C. A13
D. C
E. EQUIVALENT LATERAL FORCE ANALYSIS PROCEDURE
F. Sds = 0.49
G. Sd1 = 0.19
H. V = 2,200
I. R = 6.5
J. S5 <= .54
K. S1 <= .29
L. CS = 0.08

SEISMIC IMPORTANCE FACTOR
SITE CLASS
SEISMIC FORCE RESISTING SYSTEM
SEISMIC DESIGN CATEGORY
SPECTRAL RESPONSE COEFFICIENT
SPECTRAL RESPONSE COEFFICIENT
DESIGN BASE SHEAR
RESPONSE MODIFICATION COEFFICIENT
MAPPED SPECTRAL RESPONSE COEFFICIENT
MAPPED SPECTRAL RESPONSE COEFFICIENT
SEISMIC RESPONSE COEFFICIENT

BUILDING OCCUPANCY:
A. CATEGORY II
B. ASCE 7-05

FLOOD LOAD:
THE MODULAR BUILDING UNITS ARE NOT DESIGNED TO BE SUBMERGED OR SUBJECTED TO WAVE ACTION
IF INSTALLED IN A FLOOD PLAIN, THE MODULAR BUILDING UNITS MUST BE INSTALLED ABOVE THE MINIMUM BASE FLOOD ELEVATION DERIVED FROM APPROPRIATE FLOOD ELEVATION MAPS FOR THE BUILDING SITES, OR BE SET ON A FOUNDATION DESIGNED FOR FLOOD LOADS




DOOR AND FRAME SCHEDULE

		DOOR		GLAZING	HWD TYPE	FRAME	STYLE	FIRE RATING	NOTES
Quantity	MARK	WD	HGT						
1	001	3'-0"	7'-0"	FULL	THUMB LATCH	ALUMINUM	STOREFRONT	--	WHITE/BRONZE W/CLOSER
1	002	3'-0"	6'-8"	--	ABS LEVER LOCK	STEEL		--	CLOSER
5	003	3'-0"	6'-8"	--	ABS PASSAGE LEVER	BRONZE REDIFRAME	IMPERIAL OAK HC	--	
2	004	3'-0"	6'-8"	--	ABS PRIVACY LEVER	BRONZE REDIFRAME	IMPERIAL OAK HC	--	
1	005	3'-0"	6'-8"	--	ABS KEYED LEVER	BRONZE REDIFRAME	IMPERIAL OAK SC	--	

WINDOW SCHEDULE

		SIZE		Style	Sill Height	FRAME/GLASS
Quantity	MARK	WIDTH	HEIGHT			
9	1	3'-0"	5'-0"	Picture	1'-8"	WHITE/LOW E INSULATED W/INTERIOR MOUNTED BURGLAR BARS (PAINTED CREAM COLOR) W/1" ALUM MINI BLINDS
1	2	4'-6"	3'-2 1/2"	Standard	3'-5 1/2"	ROUGH OPENING ONLY (WINDOW BY OTHERS ON SITE) W/QST-619S TRANSACTION DRAWER W/SPEAKER UNDER WINDOW
2	3	3'-0"	3'-0"	Picture (2)	3'-8"	FIXED CLEAR TEMPERED
1	4	3'-0"	3'-0"	Pass Through	3'-0"	FIXED WINDOW W/SPEAKER HOLE & PASS THRU W/12" PLAS LAM (BEIGE NEBULA)WRITING LEDGE (ROUNDED CORNERS) TO EXTEND 12" PAST WALL ON HALLWAY SIDE



No.	REVISION/ISSUE	Date
1	GTM CHANGES W/CUSTOMER	11.25.13
2	SO CHANGES W/GARRY	11.25.13
3	3RD PARTY REVIEW CHANGES	12.10.13
	MOVED WINDOW IN ROOM #106	
	ROOF/CEILING JOIST SPACING 16" OC	
	ADDED EMERGENCY LIGHT IN HALLWAY	

THIRD PARTY:
RADCO
5801 BENJAMIN CENTER DRIVE #102
TAMPA, FLORIDA 33634
PH: (813) 243-0370



Manufacture:
KINGS CUSTOM BUILDERS, INC
1608 US HIGHWAY 19S
ELLAVILLE, GA 31806
PH: 229-937-2538
FX: 229-937-2150

Dealer:
ROSE OFFICE SYSTEMS

Project:
KINSEL FORD

SERIAL# K0111335383 AB			
SALESPERSON: MATTHEW TAYLOR	DRAWN BY: CHRISTIE WHITE	MODEL# 28X62	APPROVAL#
CODE: TX/IBC	LABEL: TX/RADCO	Sheet:	
Date: 11.24.13	OCCUPANCY: BUSINESS	A3	
Scale: 1/4" = 1'-0"	QUOTE# MT2716 R1	COMBINED FLOOR PLAN	

SUPPLY: PEX WITH CUT OFFS
WASTE: PVC STUB THRU FLOOR

**BATHROOM ACCESSORIES BY OTHER ON SITE...KCB TO PROVIDE
BLOCKING ONLY. KCB TO INSTALL GRAB BARS ONLY**


8'-9" (BEIGE NEBULA) PLASTIC LAMINATE BASE CABINETS W/
3'-9" (BEIGE NEBULA) PLASTIC LAMINATE COUNTER TOP W/
(1) DOUBLE STAINLESS STEEL SINK W/ CHROME WRIST
BLADE GOOSENECK FAUCET

15'-4" (BEIGE NEBULA) PLASTIC LAMINATE OVERHEAD CABINETS

5BLF 8" WIDE (BAJA MELANGE) SOLID SURFACE TOP ON 60" TALL WALLS
WITH ROUNDED CORNERS

(1) 18" DEEP X 4" (BEIGE NEBULA) PLASTIC
COUNTER TOP @ 30" AFF

(1) 18" DEEP X 6"8" (BEIGE NEBULA) PLASTIC LAMINATE
COUNTER TOP @ 30" AFF



TEXAS INDUSTRIALIZED BUILDING CODE COUNCIL
This document is approved pursuant to
the Industrialized Housing and Buildings Act.

DRA No. 17 IBC ☒ IRC
Date: Dec 13, 2013 *dyg*
DRA Signature: _____



THIRD PARTY:
RADCO
5801 BENJAMIN CENTER DRIVE #102
TAMPA, FLORIDA 33634
PH: (813) 243-0370



KENNETH EARL DUNMON
PROFESSIONAL ENGINEER
AMERICUS, GEORGIA

Manufacture:
KINGS CUSTOM BUILDERS, INC
1608 US HIGHWAY 19S
ELLAVILLE, GA 31806
PH: 229-937-2538
FX: 229-937-2150




Dealer:



ROSE OFFICE SYSTEMS

Project:

KINSEL FORD

SERIAL# K01111335383 AB			
SALESPERSON MATTHEW TAYLOR	DRAWN BY: CHRISTIE WHITE	MODEL# 28X62	APPROVAL#
CODE: TX/IBC	LABEL: TX/RADCO	Sheet:	
Date: 11/24/13	OCCUPANCY: BUSINESS	P1 PLUMBING FLOW PLAN	
Scale: 1/4" = 1'-0"	QUOTE# M72716 R1		





SERIAL# K01111335383 AB			
SALESPERSON: MATTHEW TAYLOR	DRAWN BY: CHRISTIE WHITE	MODEL# 28X62	APPROVAL#
CODE: TX/IBC	LABEL: TX/RADC0	Sheet: S1 XSEC	
Date: 11.24.13	OCCUPANCY: BUSINESS		
Scale: 1/4" = 1'-0"	QUOTE# M12716 RI		

