

ACCESSIBILITY NOTES:

1. THE INTERNATIONAL SYMBOL OF ACCESSIBILITY SIGN SHALL BE DISPLAYED AT ALL ACCESSIBLE RESTROOM FACILITIES AND AT ACCESSIBLE BUILDING ENTRANCES UNLESS ALL ENTRANCES ARE ACCESSIBLE. INACCESSIBLE ENTRANCES SHALL HAVE DIRECTIONAL SIGNS INDICATING THE ROUTE TO THE NEAREST ACCESSIBLE ENTRANCE.
2. ACCESSIBLE DRINKING FOUNTAINS SHALL HAVE A SPOUT HEIGHT NO HIGHER THAN 36 INCHES ABOVE THE FLOOR AND NO LOWER THAN 34 INCHES ABOVE THE FLOOR. THE FLOOR FOR INDIVIDUALS IN WHEELCHAIRS, ADDITIONALLY, DRINKING WATER PROVISIONS SHALL BE MADE FOR INDIVIDUALS WHO HAVE DIFFICULTY BENDING.
3. WHERE STORAGE FACILITIES SUCH AS CABINETS, SHELVES, CLOSETS AND DRAWERS ARE PROVIDED AT LEAST ONE TYPE PROVIDED SHALL CONTAIN STORAGE SPACE COMPLYING WITH THE FOLLOWING: DOORS ETC. TO SUCH SPACES SHALL BE ACCESSIBLE (I.E. TOUCH LATCHES, U-SHAPED PULLS); SPACES SHALL BE 15 INCHES MINIMUM AND 48 INCHES MAXIMUM ABOVE THE FLOOR FOR FORWARD REACH OR SIDE REACH; CLOTHES RODS OR COAT HOOKS SHALL BE A MAXIMUM OF 48 INCHES ABOVE THE FLOOR (46 INCHES MAXIMUM WHEN DISTANCE FROM WHEEL CHAIR TO ROD EXCEEDS 10 INCHES). SHELVES IN KITCHENS OR TOILET ROOMS SHALL BE 40 INCHES MINIMUM AND 48 INCHES MAXIMUM ABOVE IN FLOOR.
4. CONTROLS, DISPENSERS, RECEPTACLES AND OTHER OPERABLE EQUIPMENT SHALL BE NO HIGHER THAN 48 INCHES ABOVE THE FLOOR. RECEPTACLES ON WALLS SHALL BE MOUNTED NO LESS THAN 15 INCHES ABOVE THE FLOOR. EXCEPTION: HEIGHT LIMITATIONS DO NOT APPLY WHERE THE USE OF SPECIAL EQUIPMENT DICTATES OTHERWISE OR WHERE ELECTRICAL RECEPTACLES ARE NOT NORMALLY INTENDED FOR USE BY BUILDING OCCUPANTS.
5. WHERE EMERGENCY WARNING SYSTEMS ARE PROVIDED, THEY SHALL INCLUDE BOTH AUDIBLE AND VISUAL ALARMS. THE VISUAL ALARMS SHALL BE LOCATED THROUGHOUT, INCLUDING RESTROOM, AND PLACED 80 INCHES ABOVE THE FLOOR OR 6 INCHES BELOW CEILING,WHICH--EVER IS LOWER.
6. ALL DOORS SHALL BE OPENABLE BY A SINGLE EFFORT. DOOR CLOSERS SHALL BE ADJUSTED SO THAT FROM AN OPEN POSITION OF 90 DEGREES, THE TIME REQUIRED TO MOVE THE DOOR TO AN OPEN POSITION OF 12 DEGREES SHALL BE 5 SECONDS MINIMUM. THE MAXIMUM FORCE REQUIRED FOR PULLING OR PUSHING OPEN DOORS OTHER THAN FIRE DOORS SHALL NOT EXCEED 5 LBS. FOR ALL SLIDING, FOLDING, AND INTERIOR HINGED DOORS.
7. FLOOR SURFACES SHALL BE STABLE, FIRM, AND SLIP-RESISTANT. CHANGES IN LEVEL BETWEEN 0.25 INCH AND 0.5 INCH SHALL BE BEVELED WITH A SLOPE NO GREATER THAN 1:2 CHANGES IN LEVEL GREATER THAN 0.5 INCH REQUIRE RAMPS. CARPET PILE THICKNESS SHALL BE 0.5 MAX. GRATINGS IN FLOOR SHALL HAVE SPACES NO GREATER THAN 0.5 INCH WIDE IN ONE DIRECTION. DOORWAY THRESHOLDS SHALL NOT EXCEED 0.5 INCH IN HEIGHT.
8. ACCESSIBLE WATER CLOSETS SHALL BE 17 INCHES TO 19 INCHES, MEASURED FROM THE FLOOR TO THE TOP OF THE SEAT. GRAB BARS SHALL BE 36 INCHES LONG MINIMUM WHEN LOCATED BEHIND WATER CLOSET AND 42 INCHES MINIMUM WHEN LOCATED ALONG SIDE OF WATER CLOSET, AND SHALL BE MOUNTED 33 INCHES TO 36 INCHES ABOVE THE FLOOR. IN ADDITION, A VERTICAL GRAB BAR 18 INCHES MINIMUM IN LENGTH SHALL BE MOUNTED ON THE SIDEWALL WITH THE BOTTOM OF THE BAR LOCATED BETWEEN 39 AND 41 INCHES ABOVE THE FLOOR, AND WITH THE CENTER LINE OF THE BAR LOCATED BETWEEN 39 INCHES AND 41 INCHES FROM THE REAR WALL.
9. ACCESSIBLE URINALS SHALL BE STALL-TYPE OR WALL HUNG WITH ELONGATED RIMS AT A MAXIMUM OF 17 INCHES ABOVE THE FLOOR.
10. ACCESSIBLE LAVATORIES AND SINKS SHALL BE MOUNTED WITH THE RIM NO HIGHER THAN 34 INCHES ABOVE THE FLOOR. KNEE CLEARANCE OF AT LEAST 27 INCHES HIGH MUST BE PROVIDED WITH A MINIMUM DEPTH OF 8 INCHES BENEATH THE FIXTURE, AND 9 INCHES HIGH MINIMUM WITH A MINIMUM DEPTH OF 11 INCHES BENEATH THE FIXTURE. THE KNEE SPACE MUST BE AT LEAST 30 INCHES WIDE.
11. HOT WATER AND DRAIN PIPES UNDER ACCESSIBLE LAVATORIES AND SINKS SHALL BE INSULATED OR OTHERWISE CONFIGURED TO PROTECT AGAINST CONTACT, INSULATION OR PROTECTION MATERIALS MAY BE SITE INSTALLED. THERE SHALL BE NO SHARP OR ABRASIVE SURFACES UNDER ACCESSIBLE LAVATORIES AND SINKS.
12. ACCESSIBLE LAVATORIES AND SINKS SHALL HAVE ACCESSABLE FAUCETS (I.E. LEVER-OPERATED, PUSH TYPE, ELECTRONICALLY CONTROLLED).
13. MIRRORS LOCATED ABOVE LAVATORIES, SINKS OR COUNTERS SHALL BE MOUNTED WITH THE BOTTOM EDGE OF THE REFLECTING SURFACE A MAXIMUM OF 40 INCHES ABOVE THE FLOOR. OTHER MIRRORS IN TOILET ROOMS SHALL BE MOUNTED WITH THE BOTTOM EDGE OF THE REFLECTING SURFACE 35 INCHES MAXIMUM ABOVE THE FLOOR.
14. GRAB BARS HAVING A CIRCULAR CROSS SECTION SHALL HAVE AN OUTSIDE DIAMETER OF 1.25 INCHES MINIMUM AND 2.0 INCHES MAXIMUM. THE SPACE BETWEEN THE GRAB BAR AND THE WALL SHALL BE 1.5 INCHES.
15. WATER CLOSET FLUSH CONTROL SHALL BE INSTALLED A MAXIMUM OF 36 INCHES ABOVE THE FLOOR AND SHALL BE LOCATED ON THE OPEN SIDE OF THE WATER CLOSET.
16. DOORS TO ALL ACCESSIBLE SPACES SHALL HAVE ACCESSIBLE HARDWARE (I.E. LEVER - OPERATED, PUSH TYPE, ELECTRONICALLY MOUNTED WITH OPERABLE PARTS BETWEEN 34 INCHES MINIMUM AND 48 INCHES MAXIMUM ABOVE THE FLOOR).
17. TOILET STALL DOORS SHALL BE THE SELF-CLOSING TYPE.
18. A TOWEL DISPENSER SHALL BE LOCATED ADJACENT TO ALL ACCESSIBLE LAVTORIES.

GENERAL NOTES:

1. ACCESS TO BUILDING FOR PERSONS IN WHEELCHAIRS IS DESIGNED BY AND FIELD BUILT BY OTHERS AND SUBJECT TO LOCAL JURISDICTION APPROVAL. THE PRIMARY ENTRANCE MUST BE ACCESSIBLE.
2. ALL DOORS SHALL BE OPENABLE FROM THE EGRESS SIDE WITHOUT THE USE OF A KEY, TOOL, SPECIAL KNOWLEDGE OR EFFORT. MANUALLY OPERATED FLUSH BOLTS OR SURFACE BOLTS SHALL NOT BE USED.
3. ALL GLAZING WITHIN A 24 INCH ARC OF DOORS, WHOS BOTTOM EDGE IS LESS THAN 60 INCHES ABOVE THE FLOOR, AND ALL GLAZING IN DOORS SHALL BE SAFETY, TEMPERED OR ACRYLIC PLASTIC SHEET.
4. ALL STEEL STRAPS REFERENCED ON FLOOR PLAN SHALL BE 1.5 INCH x 26 GA. WITH 7 - 15 GA. x 7/16 INCH NAILS EACH END OF STRAP OR EQUIVALENT FROM RIDGE BEAM TO COLUMN, AND COLUMN TO FLOOR.
5. PORTABLE FIRE EXTINGUISHER PER N.F.P.A. - 10 INSTALLED BY OTHERS ON SITE, AND SUBJECT TO LOCAL JURISDICTION.
6. PROVISIONS FOR EXIT DISCHARGE LIGHTING ARE THE RESPONSIBILITY OF THE BUILDING OWNER AND SUBJECT TO LOCAL JURISDICTION APPROVAL WHEN NOT SHOWN ON THE FLOOR PLAN (INCLUDING EMERGENCY LIGHTING, WHEN REQUIRED).
7. WHEN LOW SIDES OF ROOF PROVIDE LESS THAN 6" OF OVERHANG, GUTTERS AND DOWN SPOUTS SHALL BE SITE INSTALLED, DESIGNED BY OTHERS, SUBJECT TO LOCAL JURISDICTION APPROVAL.
8. IN WIND-BORNE DEBRIS REGIONS, EXTERIOR GLAZING SHALL BE IMPACT RESISTANT OR PROTECTED WITH AN IMPACT RESISTANT COVERING MEETING THE REQUIREMENTS OF AN APPROVED IMPACT RESISTANT STANDARD, OR ASTM E1996. WIND-BORNE DEBRIS REGIONS ARE DESIGNATED IN SECTION 1609 OF THE IBC & FBC.
9. WINDOWS AND DOORS MUST BE CERTIFIED FOR COMPLIANCE WITH THE WIND DESIGN PRESSURE FOR COMPONENTS AND CLADDING.
10. ALL MATERIAL USED IN THE CONSTRUCTION OF THE BUILDING WHICH ARE COVERED BY THE FLORIDA BUILDING COMMISSION RULE 61G 20-3.006 SHALL HAVE CURRENT FLORIDA PRODUCT APPROVAL.
11. PLAN REVIEW AND INSPECTION REQUIRED BY CHAPTER 633 F.S. SHALL BE DONE ON SITE BY LOCAL FIRE SAFETY INSPECTOR.
12. STRAPPING MUST BE TESTED AND/OR CERTIFIED TO VERIFY THE STRUCTURAL CAPACITY. APPROPRIATE DOCUMENTATION MUST BE ON FILE AT THE MODULAR BUILDING FACILITY.
13. FIRE SAFETY PLAN REVIEW & INSPECTION IS RESERVED FOR THE LOCAL AUTHORITY HAVING JURISDICTION.
14. WINDOWS AND DOORS MUST BE CERTIFIED FOR COMPLIANCE WITH THE WIND DESIGN PRESSURE FOR COMPONENTS AND CLADDING.
15. THESE PLANS COMPLY WITH THE 2020 FBC 7TH EDITION.
16. THIS BUILDING SHALL NOT BE LOCATED TO THE SEAWARD SIDE OF THE COASTAL CONSTRUCTION LINE.
17. THE SEALED SET OF PLANS ARE ON FILE IN THE THIRD PARTY AGENCY OFFICE AS DIRECTED BY DBPR.
18. EGRESS FROM THE BUILDING TO BE DESIGNED BY OTHERS AND INSTALLED ON SITE BY OTHERS SUBJECT TO REVIEW AND APPROVAL BY THE LOCAL AUTHORITY HAVING JURISDICTION.

COMPLIANCE WITH LOCAL CODES: RULE 110-2-4-03: ALL INDUSTRIAL BUILDINGS BEARING AN INSIGNIA OF APPROVAL ISSUED BY THE COMMISSIONER PURSUANT TO THESE RULES SHALL BE HELD TO COMPLY WITH THE REQUIREMENTS ENACTED BY ANY LOCAL GOVERNMENT THAT ARE APPLICABLE TO THE MANUFACTURER AND INSTALLATION OF SUCH BUILDINGS. THE DETERMINATION BY THE DCA COMMISSIONER OF THE SCOPE OF SUCH APPROVAL IS FINAL.

ELECTRICAL NOTES:

1. ALL CIRCUITS AND EQUIPMENT SHALL BE GROUNDED IN ACCORDANCE WITH THE APPROPRIATE ARTICLES OF THE NATIONAL ELECTRICAL CODE (NEC).
2. WHEN LIGHT FIXTURES ARE INSTALLED IN CLOSETS THEY SHALL BE SURFACE MOUNTED OR RECESSED INCANDESCENT FIXTURES SHALL HAVE COMPLETELY ENCLOSED LAMPS. SURFACE MOUNTED INCANDESCENT FIXTURES SHALL HAVE A MINIMUM CLEARANCE OF 12 INCHES AND ALL OTHER FIXTURES SHALL HAVE A MINIMUM CLEARANCE OF 6 INCHES FROM "CLOSET STORAGE SPACE" AS DEFINED BY NEC ARTICLE 410.2.
3. WHEN WATER HEATERS ARE INSTALLED THEY SHALL BE PROVIDED WITH READILY ACCESSIBLE DISCONNECTS ADJACENT TO THE WATER HEATERS SERVED. THE BRANCH CIRCUIT SWITCH OR CIRCUIT BREAKER SHALL BE PERMITTED TO SERVE AS THE DISCONNECTING MEANS ONLY WHERE THE SWITCH OR CIRCUIT BREAKER IS WITHIN SIGHT FROM THE WATER HEATER OR IS CAPABLE OF BEING LOCKED IN THE OPEN POSITION.
4. HVAC EQUIPMENT SHALL BE PROVIDED WITH READILY ACCESSIBLE DISCONNECTS ADJACENT TO THE EQUIPMENT SERVED. A UNIT SWITCH WITH A MARKED "OFF" POSITION THAT IS A PART OF THE HVAC EQUIPMENT AND DISCONNECTS ALL UNGROUNDED CONDUCTORS SHALL BE PERMITTED AS THE DISCONNECTING MEANS WHERE OTHER DISCONNECTING MEANS ARE ALSO PROVIDED BY A READILY ACCESSIBLE CIRCUIT BREAKER.
5. PRIOR TO ENERGIZING THE ELECTRICAL SYSTEM THE INTERRUPTING RATING OF THE MAIN BREAKER MUST BE DESIGNED AND VERIFIED AS BEING IN COMPLIANCE WITH ARTICLES 110-9 AND 110.10 OF THE NEC BY LOCAL ELECTRICAL CONSULTANT.
6. THE MAIN ELECTRICAL PANELS AND FEEDERS ARE DESIGNED BY OTHERS, SITE INSTALLED AND SUBJECT TO LOCAL JURISDICTION APPROVAL.
7. ALL CIRCUITS CROSSING OVER MODULE MATING LINE(S) SHALL BE SITE CONNECTED WITH APPROVED ACCESSIBLE JUNCTION BOXES, OR CABLE CONNECTORS.
8. ALL RECEPTACLES INSTALLED IN WET LOCATIONS (EXTERIOR) SHALL BE IN WEATHER PROOF (WP) ENCLOSURES. THE INTEGRITY OF WHICH IS NOT AFFECTED WHEN AN ATTACHMENT PLUG CORD IS INSERTED OR REMOVED. THE RECEPT ITSELF SHALL ALSO BE LISTED FOR DAMP AND WET LOCATIONS.
9. EXTERIOR LIGHTS NOT INTENDED FOR 24 HOUR USE SHALL BE CONNECTED TO A PHOTOCELL OR TIMER.

PLUMBING NOTES:

1. TOILETS SHALL BE ELONGATED WITH NONABSORBENT OPEN FRONT SEATS.
2. REST ROOM WALLS SHALL BE COVERED WITH NONABSORBENT MATERIAL TO A MINIMUM HEIGHT OF 48 INCHES A.F.F. FLOORS SHALL HAVE A SMOOTH, HARD, NONABSORBENT SURFACE THAT EXTENDS UPWARD ONTO THE WALLS AT LEAST 6 INCHES.
3. THIS BUILDING SHALL BE CONNECTED TO A PUBLIC WATER SUPPLY AND SEWER SYSTEM IF THESE ARE AVAILABLE.
4. ALL PLUMBING FIXTURES SHALL HAVE SEPARATE SHUTOFF VALVES.
5. WATER HEATER SHALL HAVE SAFETY PAN WITH 1 INCH DRAIN TO EXTERIOR, T&P RELIEF VALVE WITH DRAIN TO WITHIN 2' TO 6" OF SAFETY PAN, AND A SHUT OFF VALVE WITHIN 3 FEET ON A COLD-WATER SUPPLY LINE.
6. DWV SYSTEM SHALL BE EITHER ABS OR PVC - DWV.
7. WATER SUPPLY LINES SHALL BE PVC OR COPPER, AND SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURERS LIMITATIONS AND INSTRUCTIONS.
8. WATER CLOSETS ARE TANK TYPE AND URINALS ARE FLUSH TANK TYPE UNLESS OTHERWISE SPECIFIED.
9. BUILDING DRAIN AND CLEANOUTS ARE DESIGNED AND SITE INSTALLED BY OTHERS, SUBJECT TO LOCAL JURISDICTION APPROVAL.
10. SHOWERS SHALL BE CONTROLLED BY AN APPROVED MIXING VALVE WITH A MAXIMUM WATER OUTLET TEMPERATURE OF 120°F (48.8°C).
11. THERMAL EXPANSION DEVICE, IF REQUIRED BY WATER HEATER INSTALLED, AND IF NOT SHOWN ON PLUMBING PLAN, IS DESIGNED AND SITE INSTALLED BY OTHERS, SUBJECT TO LOCAL APPROVAL.
12. WATER PIPES INSTALLED IN A WALL EXPOSED TO THE EXTERIOR SHALL BE LOCATED ON THE HEATED SIDE OF THE WALL INSULATION.
13. WATER, SOIL, AND WASTE PIPES IN UNCONDITIONED SPACE SHALL BE INSULATED AND PROTECTED FROM FREEZING.
14. TEMPERATURE ACTUATED MIXING VALVES WHICH ARE INSTALLED TO REDUCE WATER TEMP. TO DEFINE LIMITS, SHALL COMPLY WITH ASSE 1017.
15. TEMPERED WATER SHALL BE SUPPLIED THROUGH A WATER TEMP LIMITING DEVICE THAT CONFORMS TO ASSE 1070 AND SHALL LIMIT THE TEMPERED WATER TO A MAX OF 110°F(43°C)
17. CUSTOMER ASSUMES ALL RESPONSIBILITY FOR REQUIRED PLUMBING FIXTURES WHEN NOT SHOWN ON PLAN
18. WHEN RESTROOM FACILITIES AND/OR PLUMBING FIXTURES REQUIRED PER CODE ARE NOT PROVIDED WITHIN THE BUILDING, A HANDICAPPED ACCESSIBLE FACILITY MUST BE PROVIDED ON SITE WITHIN THE ALLOWABLE DISTANCE PER CODE. THE REQUIRED FACILITY SHALL BE THE RESPONSIBILITY OF THE BUILDING OWNER AND IS SUBJECT TO THE REVIEW AND APPROVAL OF THE LOCAL JURISDICTION HAVING AUTHORITY. THIS NOTE SHALL BE INDICATED ON THE DATA PLATE.

MECHANICAL NOTES:

1. ALL SUPPLY AIR REGISTERS SHALL BE 24 INCHES x 24 INCHES ADJUSTABLE WITH OVERHEAD FIBERGLASS DUCT (SEE FLOOR PLAN FOR SIZES), UNLESS OTHERWISE SPECIFIED. DUCTS IN UNCONDITIONED SPACES SHALL HAVE R-6 MINIMUM INSULATION AND R-8 INSULATION WHERE LOCATED OUTSIDE THE BUILDING.
2. INTERIOR DOORS SHALL BE UNDERCUT 1.5 INCHES ABOVE FINISHED FLOOR FOR AIR RETURN AND/OR AS NOTED ON FLOOR PLAN.
3. HVAC EQUIPMENT SHALL BE EQUIPPED W/OUTSIDE FRESH AIR INTAKES PROVIDING 5 CFM PER OCCUPANT & 0.06 CFM PER S.F. OF BLDG. AREA PER SECTION 403.3 OF IMC.
4. EXHAUST FANS SHALL PROVIDE A MINIMUM OF 70 CFM FOR EACH WATER CLOSET AND URINAL AND VENT THROUGH THE ROOF
5. VENT FANS SHALL BE DUCTED TO THE EXTERIOR AND TERMINATE AT AN APPROVED VENT CAP.
6. THERMOSTATS MUST BE PROGRAMMABLE.

MANUFACTURER'S DATA PLATE, STATE LABELS, AND THIRD PARTY LABEL ARE TO BE LOCATED ADJACENT TO THE ELECTRICAL PANEL.

FOUNDATION:
IN ACCORDANCE WITH THE REQUIREMENTS OF THE FLORIDA DEPARTMENT OF BUSINESS AND PROFESSIONAL REGULATION, THESE BUILDING PLANS DO NOT CONTAIN FOUNDATION SUPPORT AND TIE DOWN SYSTEM DETAILS AND SPECIFICATIONS. THE ARCHITECT/ENGINEER OF BUILDING PLANS SHOULD BE CONTACTED TO OBTAIN APPROPRIATE FOUNDATION PLANS. IF FOUNDATION PLANS ARE DESIGNED BY OTHERS, THE ARCHITECT/ENGINEER OF THE BUILDING PLANS SHALL NOT BE HELD RESPONSIBLE OF LIABLE FOR THE FOUNDATION DESIGN AND CONSEQUENTIAL PERFORMANCE OF THE SUPERSTRUCTURE'S STRUCTURAL COMPONENTS AND SYSTEMS RELATING THERETO.

BUILDING SITE INSTALLATION REQUIREMENTS

NOTE THAT THIS LIST DOES NOT NECESSARILY LIMIT THE ITEMS OF WORK AND MATERIALS THAT MAY BE REQUIRED FOR A COMPLETE INSTALLATION. ALL SITE RELATED ITEMS ARE SUBJECT TO LOCAL JURISDICTION APPROVAL.

1. FOOTINGS, FOUNDATION WALLS, PIERS, AND TIE DOWNS.
2. UTILITY CONNECTIONS AND PLUMBING LINES TO BE INSTALLED.
3. ELECTRICAL SERVICE HOOK-UP (INCLUDING FEEDERS) TO THE BUILDING.
4. THE MAIN ELECTRICAL PANEL AND SUB-FEEDERS (MULTI-UNITS ONLY).
5. CONNECTIONS OF ELECTRICAL CIRCUITS CROSSING OVER MODULE MATING LINE(S)-(MULTI-UNITS ONLY).
6. INCLUDE NOTICE OF HANDICAPPED PROVISIONS TO BE INSTALLED ON SITE.
7. RAMPS, STAIRS AND GENERAL ACCESS TO THE BUILDING.
8. STRUCTURAL AND AESTHETIC INTERCONNECTIONS BETWEEN MODULES (MULTI-UNITS ONLY).
9. TWO PRINTED SETS OF "SET-UP INSTRUCTIONS" SHALL ACCOMPANY EACH BUILDING OR COMPONENT WHEN IT LEAVES THE MANUFACTURE FACILITY.
10. BUILDING DRAINS, CLEANOUTS, SINKING FOUNTAIN, AND SERVICE SINK & HOOK UP TO PLUMBING SYSTEM.
11. GLAZED OPENING PROTECTION (SEE GENERAL NOTE NO. 8).
12. THE FLOOR AND ROOF DESIGN OF THIS PLAN IS LIGHT FRAME TRUSS-TYPE CONSTRUCTIONS: AS REFERENCED IN FAC RULE 699-3.01(6), POSTING OF NOTICE SIGN(S) AS REQUIRED BY FAC 699-3.01(6), SHALL BE SITE INSTALLED AND IS THE RESPONSIBILITY OF THE BUILDING OWNER.
13. ALL METAL FRAMING MEMBERS SHALL BE BONDED TO THE BUILDING ELECTRICAL SYSTEM AND IS THE RESPONSIBILITY OF THE BUILDING OWNER.
14. HANDICAP TACTILE SIGNAGE.
15. FLORIDA FIRE PREVENTION CODE PLAN REVIEW AND INSPECTION SHALL BE PERFORMED ON SITE BY OTHERS, SUBJECT TO LOCAL APPROVAL.

AL CODES AND LOADS

BUILDING	2015 IBC / 2015 IFC
PLUMBING	2015 IPC
MECHANICAL	2015 IMC
ELECTRICAL	2014 NEC
ENERGY	2015 IECC
ACCESSIBILITY	2010 ADA

FL CODES



BUILDING CODE	2020 FBC 7TH EDITION-BUILDING
PLUMBING CODE	2020 FBC 7TH EDITION-PLUMBING
MECH. CODE	2020 FBC 7TH EDITION-MECHANICAL
ELECTRICAL CODE	2017 NEC
LIFE SAFETY	2018 FFPC
ENERGY	2020 FBC ENERGY CONSERVATION, 7TH EDITION
ACCESSIBILITY	2020 FBC 7TH EDITION-ACCESSIBILITY
FIRE	2020 FFPC 7TH EDITION
	2018 NFPA 1 UFC AND 2018 NFPA 101

LOUISIANA NOTES:

1. EXTERIOR SITE RELATED ITEMS SHALL BE ADDRESSED BY THE LOCAL ENGINEER AND OR CONTRACTOR, AND ARE OUT OF THE LIMITATIONS OF THIS APPROVAL. SUCH ITEMS ARE INCLUDING, BUT NOT LIMITED TO: RAMPS SITE PLAN, PARKING SPACES, LOCATION OF BUILDING WITH RESPECT TO PROPERTY LINES, EXTERIOR LIGHTING, ACCESS TO PUBLIC WAYS, STAIRS HAND RAILS AND SITE RELATED UTILITIES.
2. THIS APPROVAL IS FOR THE BUILDING DESIGN AND CONSTRUCTION ONLY.
3. ALL ACCESSIBILITY RELATED ITEMS LISTED ARE BASED ON THE 28 CFR PART 36, OF THE ADA STANDARDS FOR ACCESSIBLE DESIGN.
4. THE CENTERLINE OF ACCESSIBLE TOILETS SHALL BE 16" FROM THE NEAREST ADJACENT WALL.
5. LAVATORIES SHALL MEET THE CRITERIA LISTED IN ACCESS NOTES.
6. HOT WATER DRAIN PIPES SHALL BE INSULATED OR COVERED.
7. FAUCETS SHALL MEET THE CRITERIA LISTED IN ACCESS NOTES.
8. MIRRORS SHALL MEET THE CRITERIA LISTED IN ACCESS NOTES.
9. TOILETS ROOM GRAB BARS SHALL COMPLY WITH ACCESS NOTES.
10. A 60" DIAMETER CLEAR FLOOR SPACE SHALL BE PROVIDED WITHIN EACH OCCUPIABLE ROOM FOR TURNING.
11. ALL DOORS PROVIDED PROVIDE A MINIMUM 32" CLEAR WIDTH.
12. MANEUVERING CLEARANCES AT DOORS COMPLY WITH FIGURE 404.2.4
13. THRESHOLDS SHALL COMPLY WITH ACCESS NOTES.
14. CHANGES IN FLOOR ELEVATIONS SHALL COMPLY WITH ACCESS NOTES.
15. SEE NOTE #1 REGARDING RAMPS AND STAIRS.
16. PERMANENT SIGNAGE SHALL COMPLY WITH ADA 703.1
 - A. SIGNAGE, WHERE PROVIDED FOR PERMANENT ROOMS AND SPACES SHALL PROVIDE:1. BRAILLE AND RAISED LETTERING AS PER ADA 703.1
 2. LETTER/SYMBOL TO BACKGROUND COLOR CONTRAST PER ADA 703.5.1
 3. TACTILE SIGNS SHALL BE BETWEEN 48"-60" A.F.F. PER ADA 703.4B. OTHER PERMANENT SIGNS WHICH PROVIDE DIRECTION TO OR IN INFORMATION ABOUT FUNCTIONAL SPACES OF THE BUILDING SHALL PROVIDE:1. LETTER CHARACTER WIDTH TO HEIGHT PROPORTION PER ADA 703.5.4
2. CHARACTER HEIGHT PROPORTION BASED ON HEIGHT OF SIGN FROM FINISH FLOOR PER ADA 703.5.5
3. LETTER/SYMBOL TO BACKGROUND COLOR CONTRAST PER ADA 703.5.1.
17. LOOKS ON DOORS IN MEANS OF EGRESS SHALL NOT REQUIRE THE USE OF A KEY, SPECIAL DEVICE OR SPECIAL KNOWLEDGE TO OPEN.
18. DOOR SHALL BE CAPABLE OF BEING OPENED WITH ONLY ONE RELEASING OPERATION, KNOBS W/INDEPENDENT SLIDE BOLTS ARE NOT ACCEPTABLE.
19. INTERIOR WALLS AND CEILINGS SHALL HAVE A FLAME SPREAD OF 0-200 AND A SMOKE DEVELOPED RATING OF 0-450.
20. FIRE EXTINGUISHERS, INSTALLED ON SITE BY OTHERS, SHALL COMPLY WITH NFPA 10.

PRODUCT APPROVAL INFORMATION:

1. CECO DOORS (IMPACT)	-	FLA.#	4553--R13
2. JELD-WEN WINDOWS (IMPACT)	-	FLA.#	11120-R15
3. HARDI PANEL SIDING	-	FLA.#	13223.2-R5
4. (MULEHIDE) ROOF	-	FLA.#	10703-R9



03-16-2021

03-16-2021

03-16-2021

BUILDING DESIGN PARAMETERS

1. USE/OCCUPANCY: **BUSINESS**
2. CONSTRUCTION TYPE: **V/B**
3. SPRINKLER SYSTEM: **NO**
4. BUILDING AREA: **2460 SF.**
5. BUILDING HEIGHT: **≤ 16 FEET**
6. NUMBER OF STORIES: **1**
7. NUMBER OF MODULES: **3**
- 8A. 49 PEOPLE TOTAL FROM 14 PEOPLE @ 100 SF/P IN OFFICES AREAS AND 35 IN @ 15 SF/P BREAK AREA
- 8B. 45 PEOPLE TOTAL FROM 10 PEOPLE @ 150 SF/P IN OFFICES AREAS AND 35 IN BREAK AREA (2018 IBC ONLY)
9. EXTERIOR WALL FIRE RATING: **NOT RATED**
10. THIS BUILDING MUST BE INSTALLED WITH THE FIRE SEPARATION DISTANCES REQUIRED BY IBC TABLE 602 AND SECTION 705.3. OF IBC
11. ENRGERY CODE COMPLIANCE: SEE ATTACHED ENERGY CALCULATIONS.
12. MANUFACTURER'S DATA PLATE, STATE LABELS AND THIRD PARTY LABELS ARE TO BE LOCATED ADJACENT TO ELECTRICAL PANEL.

MS CODES AND LOADS

BUILDING CODE	2012 IBC
PLUMBING CODE	2012 IPC
MECH. CODE	2012 IMC
NEC	2011 NEC
INTERNATIONAL FIRE CODE	2012 IFC
LIFE SAFETY CODE	2012 NFPA 101
INTERNATIONAL	2010 ASHRAE
ENERGY CONSERVATION CODE	2010 ASHRAE
ACCESSIBILITY	ANSI-2009

LA CODES

BUILDING CODE	2015 IBC EX. CH. 1, 11, 29 W/ AMENDS.
PLUMBING CODE	2015 W/ AMENDS.
MECH. CODE	2015 IMC
ELECTRICAL CODE	2014 NEC
LIFE SAFETY	2015 NFPA 101 DELETE CH.5
ENERGY	ASHRAE 90.1-2007
ACCESSIBILITY	ADASAD 2010

GA CODES

BUILDING CODE	2018 IBC W/ 2020 GA AMENDMENTS
PLUMBING CODE	2018 IPC W/ 2020 GA AMENDMENTS
MECH. CODE	2018 IMC W/ 2020 GA AMENDMENTS
ELECTRICAL	2020 NEC W/ NO GA AMENDS
FIRE CODE	2018 IFC W/ GA AMENDMENTS
LIFE SAFETY CODE	CHAPTER 120-3-3, GA STATE MINIMUM FIRE SAFETY STANDARDS & 2018 LIFE SAFETY CODE W/ GA AMENDMENTS
ENERGY	2015 IECC W/ 2020 GA AMENDMENTS
ACCESSIBILITY	120-3-30 GA ACCESSIBILITY CODE & 2010 ADA STANDARDS

DRAWING INDEX	
SHT	DESCRIPTION
1	COVER SHEET / NOTES
2	ELEVATIONS
3	COMBINED FLOOR PLAN
4	FLOOR PLAN
5	T-GRID PLAN
6	ELECTRICAL FLOOR PLAN
7	PLUMBING FLOOR PLAN
8	MECHANICAL FLOOR PLAN
9	CROSS SECTION
1-1	FOUNDATION

WINDOW & DOOR SPECIFICATIONS

1. DBL. PANE WINDOWS ARE REQUIRED FOR ALL CLIMATE ZONES. SEE THE COMCHECK ENERGY CALCULATIONS FOR THE MAXIMUM ALLOWED U-FACTOR AND SHGC.
2. THE MAXIMUM ALLOWABLE AIR LEAKAGE RATE FOR WINDOWS IS 0.3 CFM PER SQUARE FEET OF WINDOW AREA.
3. THE MAXIMUM ALLOWABLE AIR LEAKAGE RATE FOR EXTERIOR DOORS IS 0.3 CFM PER SQUARE FEET OF DOOR AREA.

FL-STRUCTURAL LOAD LIMITATION

FLOOR LIVE LOAD:

- A. 50 PSF OFFICES / 100 PSF CORRIDORS / 100 PSF BREAK AREA
- B. 2,000 LB.-. CONCENTRATED LOAD OVER 30"x30" AREA LOCATED ANYWHERE ON FLOOR

ROOF LIVE LOAD:

- A. 20 PSF

BUILDING ENCLOSURE: ENCLOSED

ROOF SNOW LOAD: N/A

WIND LOAD:

- A. BASIC WIND SPEED (3 SEC GUST) V= 140 MPH (HVHZ)
- B. ASD WIND SPEED (3 SEC GUST) ASD= 109 MPH (HVHZ)
- C. RISK CATEGORY: II (ASSE 7-16)
- D. WIND EXPOSURE CATEGORY: C
- E. INTERNAL PRESSURE COEFFICIENT Gcpi = 0.18
- F. WIND IMPORTANCE FACTOR Iw= 1.0
- G. WALL ZONE 5: P = +/-57.1 PSF (Posd = +/-34.3 PSF)
WALL ZONE 4: P = +/-46.2 PSF (Posd = +/-27.7 PSF)
ROOF ZONE 3: P = -122.2 PSF (Posd = -73.3 PSF)
ROOF ZONE 2: P = -89.7 PSF (Posd = -53.8 PSF)
ROOF ZONE 1: P = -68.0 PSF (Posd = -40.8 PSF)
ROOF ZONE 1': P = -39.1 PSF (Posd = -23.5 PSF)

H. THIS BUILDING IS NOT DESIGNED FOR PLACEMENT ON THE UPPER HALF OF A HILL OR ESCARPMENT EXCEEDING 15 FEET IN HEIGHT.

SEISMIC LOAD: N/A

FLOOD LOAD:

THIS BUILDING IS NOT DESIGNED TO BE SUBMERGED BELOW THE BASE FLOOD ELEVATION IN A FLOOD HAZARD AREA.

THIS BUILDING HAS NOT BEEN DESIGNED FOR USE IN HIGH VELOCITY HURRICANE ZONES (HVHZ). HVHZ ZONES CONSIST OF BROWARD AND MIAMI-DADE COUNTIES

LISTING

AGENCY APPROVAL

THESE PRINTS COMPLY WITH THE FLORIDA MANUFACTURED BUILDING ACT OF 1979 CONSTRUCTION CODE AND ADDHERE TO THE FOLLOWING CRITERIA.



CONST. TYPE	VB
OCCUPANCY	BUSINESS
ALLOWABLE NO. OF FLOORS	1
WIND VELOCITY OF EXT. WALLS	140VULT 109VASD
FIRE RATING OF EXT. WALLS	0
PLAN NO.	PMM-20680
ALLOW. FLOOR LOAD	50/100
APPROVAL DATE	3-16-21
MANUF.	PMM
HIGH VELOCITY HURRICANE ZONE	NO

EMC

EMC

WALTER WOOD, P.E.

168 W. LONGLEAF DR.
SYLVESTER, GA 31791



03-16-2021

03-16-2021

WALTER WOOD, P.E.
CONSULTING ENGINEER
168 W. LONGLEAF DR.
SYLVESTER, GA 31791

PRO MOD
MANUFACTURING
1619 STATE ROAD 26 WEST
ELLAUVILLE, GA 31806

DRAWN BY: T. WOOLSEY

CHECKED BY: TEAM


DATE: 2/23/2021

SCALE: N-T-S

EMC# PMM-20680 A-C


SERIAL# 20680 A-C

COVER SHEET:




FRONT ELEVATION / SOUTH

FOUNDATION ENCLOSURE (WHEN PROVIDED) SHALL HAVE
1 SQUARE FOOT NET VENT AREA PER 1/150th OF THE FLOOR AREA.




REAR ELEVATION / NORTH

HANDICAP RAMP, STAIRS, AND HANDRAILS
SITE INSTALLED, DESIGNED BY OTHERS, AND
SUBJECT TO LOCAL CODE INSPECTION.



RIGHT ELEVATION / EAST

SEE CROSS SECTION FOR
ROOF VENTILATION METHOD.



LEFT ELEVATION / WEST




PROJECT HISTORY
START DATE: 2/23/2021

ROSE OFFICE SYSTEMS

TYNDALL AFB

SERIAL No.: SME-20680 A-C

WALTER WOOD, P.E.
CONSULTING ENGINEER
168 W. LONGLEAF DR.
SYLVESTER, GA 31791



DRAWN BY: T. WOOLSEY
CHECKED BY: TEAM
DATE: 2/23/2021
SCALE: N-T-S
EMC# PMM-20680 A-C
SERIAL# 20680 A-C
ELEVATIONS SHEET:


3 OF 9

SYMBOL LEGEND	
PANEL BOX	SINGLE SWITCH
DUPLEX RECEPTACLE 120v	DOUBLE SWITCH
PORCH LIGHT	4-WAY SWITCH
EXT. WEATHERPROOF GFI REC.	EMERGENCY LIGHT
VENT FAN	XRS EMERGENCY LIGHT
DEDICATED RECEPT	DUAL REMOTE HEAD
RECEPT UNDER FLOOR MT.	WALL OCCUPANCY SENSOR
2x4 39WATT LED LIGHT FIX.	DIRECTIONAL EXIT SIGN
ICEMAKER BOX	24"x24" RETURN AIR GRILLE (CEILING)
THERMOSTAT	24"x24" SUPPLY AIR DIFFUSER (CEILING)

NOTE: ALL WALL DIMENSIONS ARE TO WALL FINISH AND NOT TO THE STUD!!!

NOTE: ALL HEIGHTS SPECIFIED A.F.F. (ABOVE FINISHED FLOOR) ARE MEASURED TO THE BOTTOM OF THE OBJECT OR ITEM.

COLOR CHART	
	WALLS
	WINDOWS
	DOORS
	ELECTRICAL
	WIRING
	HVAC / DUCT / DIFFUSERS
	DIMENSIONS
	TRUSS BAYS
	PLUMBING



DOOR AND FRAME SCHEDULE									
Quantity	MARK	DOOR		GLAZING	HWD TYPE	FRAME	STYLE	FIRE RATING	NOTES
		WD	HGT						
3	001	3'-0"	6'-8"	4X25(SAFETY GLASS)	TELL GRADE 2 KEYED LEVER	STEEL	STEEL	N/A	TELL 6000 SERIES CLOSER
2	002	3'-0"	6'-8"	N/A	TELL GRADE 2 PRIVACY LEVER	REDIFRAME	6 PANEL COLONIST SC	20 MIN.	FLOOR MT. DOORS STOPS
1	003	3'-0"	6'-8"	N/A	TELL GRADE 2 KEYED LEVER	REDIFRAME	6 PANEL COLONIST SC	20 MIN.	FLOOR MT. DOOR STOPS
1	004	4'-0"	6'-8"	N/A	N/A	N/A	CASED OPENING	N/A	N/A

WINDOW SCHEDULE						
Quantity	MARK	SIZE		Style	Sill Height	FRAME/GLASS
		WIDTH	HEIGHT			
9	1	3'-0"	5'-0"	Single Hung	1'-8"	V/S WHITE VINYL W/ LOWE INSULATED GLASS & PVC MINIBLINDS

EMC R. JOHNSON APPROVED 03 16 2021

WALTER WOOD, P.E.
168 W. LONGLEAF DR.
SYLVESTER, GA 31791

PROJECT HISTORY
START DATE: 2/23/2021

ROSE OFFICE SYSTEMS
TYNDALL AFB
SERIAL No.: SME-20680 A-C

WALTER WOOD, P.E.
CONSULTING ENGINEER
168 W. LONGLEAF DR.
SYLVESTER, GA 31791

PRO MOD MANUFACTURING
1619 STATE ROAD 26 WEST
ELLAVILLE, GA 31806


DRAWN BY: T. WOOLSEY
CHECKED BY: TEAM
DATE: 2/23/2021
SCALE: N-T-S
EMC# PMM-20680 A-C
SERIAL# 20680 A-C
FLOOR PLAN SHEET:
4 OF 9

SYMBOL LEGEND	
PANEL BOX	SINGLE SWITCH
DUPLEX RECEPTACLE 120v	DOUBLE SWITCH
PORCH LIGHT	4-WAY SWITCH
EXT. WEATHERPROOF GFI REC.	EMERGENCY LIGHT
VENT FAN	XR5 EMERGENCY LIGHT
DEDICATED RECEPT	DUAL REMOTE HEAD
RECEPT UNDER FLOOR MT.	WALL OCCUPANCY SENSOR
2X4 39WATT LED LIGHT FIX.	DIRECTIONAL EXIT SIGN
ICEMAKER BOX	24"x24" RETURN AIR GRILLE (CEILING)
THERMOSTAT	24"x24" SUPPLY AIR DIFFUSER (CEILING)

NOTE: ALL WALL DIMENSIONS ARE TO WALL FINISH AND NOT TO THE STUD!!!

NOTE: ALL HEIGHTS SPECIFIED A.F.F. (ABOVE FINISHED FLOOR) ARE MEASURED TO THE BOTTOM OF THE OBJECT OR ITEM.

COLOR CHART	
	WALLS
	WINDOWS
	DOORS
	ELECTRICAL
	WIRING
	HVAC / DUCT / DIFFUSERS
	DIMENSIONS
	TRUSS BAYS
	PLUMBING



R. JOHNSON
APPROVED
03 16 2021

WALTER WOOD, P.E.
168 W. LONGLEAF DR.
SYLVESTER, GA 31791

PROJECT HISTORY
START DATE: 2/23/2021

ROSE OFFICE SYSTEMS
TYNDALL AFB
SERIAL NO.: SME-20680 A-C

WALTER WOOD, P.E.
CONSULTING ENGINEER
168 W. LONGLEAF DR.
SYLVESTER, GA 31791

PRO MOD MANUFACTURING
1619 STATE ROAD 26 WEST
ELLAVILLE, GA 31806

DRAWN BY: T. WOOLSEY
CHECKED BY: TEAM
DATE: 2/23/2021
SCALE: N-T-S
EMC# PMM-20680 A-C
SERIAL# 20680 A-C
T-GRID LAYOUT SHEET:
5 OF 9


SYMBOL LEGEND	
PANEL BOX	SINGLE SWITCH
DUPLEX RECEPTACLE 120v	DOUBLE SWITCH
PORCH LIGHT	4-WAY SWITCH
EXT. WEATHERPROOF GFI REC.	EMERGENCY LIGHT
VENT FAN	XR5 EMERGENCY LIGHT
DEDICATED RECEPT	DUAL REMOTE HEAD
RECEPT UNDER FLOOR MT.	WALL OCCUPANCY SENSOR
2X4 19WATT LED LIGHT FIX.	24"x24" RETURN AIR GRILLE (CEILING)
ICEMAKER BOX	24"x24" SUPPLY AIR DIFFUSER (CEILING)
THERMOSTAT	

NOTE: ALL WALL DIMENSIONS ARE TO WALL FINISH AND NOT TO THE STUD!!!

NOTE: ALL HEIGHTS SPECIFIED A.F.F. (ABOVE FINISHED FLOOR) ARE MEASURED TO THE BOTTOM OF THE OBJECT OR ITEM.

COLOR CHART

- WALLS
- WINDOWS
- DOORS
- ELECTRICAL
- WIRING
- HVAC / DUCT / DIFFUSERS
- DIMENSIONS
- TRUSS BAYS
- PLUMBING






A 150 AMP PANEL							
REL. NO.	DESCRIPTION	BRKR	WIRE SIZE	REL. NO.	DESCRIPTION	BRKR	WIRE SIZE
1	HVAC	60	6	2	RECEPTS	20	12
3	HVAC	60	6	4	RECEPTS	20	12
5				6			
7				8			
9				10			
11				12			
13				14			
15				16			
MIN. CODE LTG. VA $0 \times 0 \times 3.5 = 0$ VA							
TOTAL PANEL VA LOAD = (CONTIN.) $0 + (NON-CONT.) 1,980 + (MOTOR) 13,920 = 15,900$ VA							
PANEL AMPS = TOTAL VA $15,900 / 240$ V = 66 AMPS + 10% GROWTH 73 AMPS							

B 150 AMP PANEL							
REL. NO.	DESCRIPTION	BRKR	WIRE SIZE	REL. NO.	DESCRIPTION	BRKR	WIRE SIZE
1	HVAC	60	6	2	RECEPTS	20	12
3	HVAC	60	6	4	RECEPTS	20	12
5	DEDICATED QUAD	20	12	6	DEDICATED QUAD	20	12
7	LIGHTING	20	12	8			
9				10			
11				12			
13				14			
15				16			
MIN. CODE LTG. VA $4,225 \times 1,207 \times 3.5 = 4,225$ VA							
TOTAL PANEL VA LOAD = (CONTIN.) $4,225 + (NON-CONT.) 5,420 + (MOTOR) 13,920 = 24,565$ VA							
PANEL AMPS = TOTAL VA $24,565 / 240$ V = 102 AMPS + 10% GROWTH 113 AMPS							

C 150 AMP PANEL							
REL. NO.	DESCRIPTION	BRKR	WIRE SIZE	REL. NO.	DESCRIPTION	BRKR	WIRE SIZE
1	HVAC	60	6	2	RECEPTS	20	12
3	HVAC	60	6	4	RECEPTS	20	12
5	DEDICATED RECEPT	20	12	6	DEDICATED GFCI	20	12
7	DEDICATED GFCI	20	12	8	DEDICATED GFCI	20	12
9	W/H	20	12	10	LIGHTING	20	12
11	LIGHTING	20	12	12	RESTROOMS	20	12
13				14			
15				16			
MIN. CODE LTG. VA $4,386 \times 1,253 \times 3.5 = 4,386$ VA							
TOTAL PANEL VA LOAD = (CONTIN.) $4,386 + (NON-CONT.) 9,540 + (MOTOR) 14,460 = 28,386$ VA							
PANEL AMPS = TOTAL VA $28,386 / 240$ V = 118 AMPS + 10% GROWTH 130 AMPS							

EMC R. JOHNSON APPROVED 03 16 2021



WALTER WOOD, P.E.
168 W. LONGLEAF DR.
SYLVESTER, GA 31791

WALTER E. WOOD
REGISTERED PROFESSIONAL ENGINEER
28380
STATE OF MISSISSIPPI

03-16-2021

PROJECT HISTORY
START DATE: 2/23/2021

ROSE OFFICE SYSTEMS
TYNDALL AFB
SERIAL No.: SME-20680 A-C

WALTER WOOD, P.E.
CONSULTING ENGINEER
168 W. LONGLEAF DR.
SYLVESTER, GA 31791

PRO MOD
MANUFACTURING
1619 STATE ROAD 26 WEST
ELLAVILLE, GA 31760




DRAWN BY: T. WOOLSEY
CHECKED BY: TEAM
DATE: 2/23/2021
SCALE: N-T-S
EMC# PMM-20680 A-C
SERIAL# 20680 A-C
ELECTRICAL SHEET:

SYMBOL LEGEND	
PANEL BOX	SINGLE SWITCH
DUPLEX RECEPTACLE 120v	DOUBLE SWITCH
PORCH LIGHT	4-WAY SWITCH
EXT. WEATHERPROOF GFI REC.	EMERGENCY LIGHT
VENT FAN	XRS EMERGENCY LIGHT
DEDICATED RECEPT	DUAL REMOTE HEAD
RECEPT UNDER FLOOR MT.	WALL OCCUPANCY SENSOR
2X4 39WATT LED LIGHT FIX.	DIRECTIONAL EXIT SIGN
ICEMAKER BOX	
THERMOSTAT	

NOTE: ALL WALL DIMENSIONS ARE TO WALL FINISH AND NOT TO THE STUD!!!

NOTE: ALL HEIGHTS SPECIFIED A.F.F. (ABOVE FINISHED FLOOR) ARE MEASURED TO THE BOTTOM OF THE OBJECT OR ITEM.

COLOR CHART	
	WALLS
	WINDOWS
	DOORS
	ELECTRICAL
	WIRING
	HVAC / DUCT / DIFFUSERS
	DIMENSIONS
	TRUSS BAYS
	PLUMBING



R. JOHNSON
APPROVED
03 16 2021

WALTER WOOD, P.E.
168 W. LONGLEAF DR.
SYLVESTER, GA 31791

PROJECT HISTORY
START DATE: 2/23/2021

ROSE OFFICE SYSTEMS
TYNDALL AFB
SERIAL No.: SME-20680 A-C

WALTER WOOD, P.E.
CONSULTING ENGINEER
168 W. LONGLEAF DR.
SYLVESTER, GA 31791

PRO MOD
MANUFACTURING
1619 STATE ROAD 26 WEST
ELLAVILLE, GA 31806


DRAWN BY: T. WOOLSEY
CHECKED BY: TEAM
DATE: 2/23/2021
SCALE: N-T-S
EMC# PMM-20680 A-C
SERIAL# 20680 A-C
PLUMBING SHEET:
9 OF 9

SYMBOL LEGEND	
PANEL BOX	SINGLE SWITCH
DUPLEX RECEPTACLE 120v	DOUBLE SWITCH
PORCH LIGHT	4-WAY SWITCH
EXT. WEATHERPROOF GFI REC.	EMERGENCY LIGHT
VENT FAN	XR5 EMERGENCY LIGHT
DEDICATED RECEPT	DUAL REMOTE HEAD
RECEPT UNDER FLOOR MT.	WALL OCCUPANCY SENSOR
2X4 39WATT LED LIGHT FIX.	DIRECTIONAL EXIT SIGN
ICEMAKER BOX	24"x24" RETURN AIR GRILLE (CEILING)
THERMOSTAT	24"x24" SUPPLY AIR DIFFUSER (CEILING)

NOTE: ALL WALL DIMENSIONS ARE TO WALL FINISH AND NOT TO THE STUD!!!

NOTE: ALL HEIGHTS SPECIFIED A.F.F. (ABOVE FINISHED FLOOR) ARE MEASURED TO THE BOTTOM OF THE OBJECT OR ITEM.

COLOR CHART	
	WALLS
	WINDOWS
	DOORS
	ELECTRICAL
	WIRING
	HVAC / DUCT / DIFFUSERS
	DIMENSIONS
	TRUSS BAYS
	PLUMBING



R. JOHNSON
APPROVED
03 16 2021

VALID
ALABAMA
LICENSED
No. 36517
PROFESSIONAL
ENGINEER
WALTER E. WOOD
03-16-2021

VALID
WALTER E. WOOD
LICENSE
No. 61323
STATE OF
MISSISSIPPI
PROFESSIONAL ENGINEER
03-16-2021

VALID
GEORGIA
REGISTERED
No. PE013043
PROFESSIONAL
ENGINEER
WALTER E. WOOD
03-16-2021

VALID
STATE OF LOUISIANA
WALTER E. WOOD
License No. 18164
PROFESSIONAL ENGINEER
03-16-2021

WALTER WOOD, P.E.
168 W. LONGLEAF DR.
SYLVESTER, GA 31791
WALTER E. WOOD
LICENSED PROFESSIONAL
ENGINEER
28580
STATE OF MISSISSIPPI
03-16-2021


PROJECT HISTORY
START DATE: 2/23/2021

ROSE OFFICE SYSTEMS
TYNDALL AFB
SERIAL NO.: SME-20680 A-C

WALTER WOOD, P.E.
CONSULTING ENGINEER
168 W. LONGLEAF DR.
SYLVESTER, GA 31791

1619 STATE ROAD 26 WEST
ELLAVILLE, GA 31806

DRAWN BY: T. WOOLSEY
CHECKED BY: TEAM
DATE: 2/23/2021
SCALE: N-T-S
EMC# PMM-20680 A-C
SERIAL# 20680 A-C
MECHANICAL SHEET:
8 OF 9



MINIMUM SOIL BEARING CAPACITY	A	MAXIMUM PIER SPACING	DESIGN LIVE LOADS
1500 PSF		8'-0"	FLOOR - 50 PSF
2000 PSF		8'-0"	ROOF - 20 PSF
3000 PSF		8'-0"	ROOF SNOW - 20 PSF
MARRIAGE WALL PIER REQUIREMENTS			
PIER NUMBER	MINIMUM SOIL BEARING CAPACITY	PIER TYPE	NUMBER OF BLACK TIE DOWN STRAPS REQ'D. (EACH MODULE)
1	2000 PSF	D	2
	3000 PSF	D	2
2	2000 PSF	C	1
	3000 PSF	C	1



FOUNDATION PLAN -NTS-
NOTE: THE FOUNDATION DIMENSIONS INDICATED ON THIS PLAN DO NOT ACCOUNT FOR GAPS THAT MAY OCCUR BETWEEN MODULES DURING THE INSTALLATION PROCESS. THE FOUNDATION CONTRACTOR SHOULD CONSULT WITH THE INSTALLATION CONTRACTOR TO DETERMINE IF ADJUSTMENTS NEED TO BE MADE PRIOR TO THE LAYOUT AND CONSTRUCTION OF THE FOUNDATION.

FOUNDATION NOTES:

1. ALL FOUNDATION CONSTRUCTION, MATERIALS, AND INSTALLATION SHALL BE IN ACCORDANCE WITH ALL APPLICABLE STATE AND LOCAL CODES.
2. TIE-DOWN STRAPS TO BE 1-1/4" x .035" TYPE-1, FINISH B, GRADE 1 ZINC COATED STEEL STRAPPING CERTIFIED BY A REGISTERED ENGINEER OR ARCHITECT AS CONFORMING WITH ASTM D3953-91. TIE DOWN STRAPS AND CONNECTING HARDWARE SHALL HAVE 3150# MINIMUM WORKING CAPACITY.
3. GROUND ANCHORS SHALL HAVE 3150# MINIMUM WORKING CAPACITY, AND SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS. DESIGN OF GROUND ANCHOR, INCLUDING SHAFT LENGTH, NUMBER AND DIAMETER OF HELICES, ETC., TO BE AS SPECIFIED BY THE GROUND ANCHOR MANUFACTURER FOR THE ACTUAL SOIL TYPE ENCOUNTERED. IF THE HOLDING OR PULLOUT CAPACITIES OF GROUND ANCHORS ARE BELOW THE VALUES SPECIFIED ABOVE THE ARCHITECT/ENGINEER MUST BE CONSULTED FOR AN ALTERNATE ANCHORAGE DESIGN.
4. THE FIRST TIE-DOWN STRAP FROM ENDWALLS SHALL NOT EXCEED 1/2 THE MAXIMUM SPACING INDICATED.
5. ALL PIERS SHALL BE CONSTRUCTED OF 8"x 16" CONCRETE MASONRY UNITS CONFORMING TO ASTM C90. MASONRY UNITS SHALL BE LAID IN TYPE M OR S MORTAR OR COVERED WITH SURFACE BONDING CEMENT INSTALLED IN ACCORDANCE WITH ITS LISTING. PIER FOOTINGS SHALL BE AS DESCRIBED ABOVE.
6. MINIMUM CONCRETE FOOTING COMPRESSIVE STRENGTH 2,500 PSI AT 28 DAYS.
7. ALL REINFORCEMENT BARS SHALL COMPLY WITH ASTM A615, GRADE 60. REINFORCEMENT BARS SHALL BE EQUALLY SPACED AND PLACED WITH 3" CLEARANCE FROM BOTTOM AND SIDES OF THE FOOTING.
8. ALL PIERS SHALL BE CAPPED WITH 4" SOLID MASONRY OR CONCRETE CAP FULL LENGTH OF PIER.
9. I-BEAM SUPPORT PIERS MAY BE INSTALLED LATERALLY (90° FROM THE ORIENTATION SHOWN ON THE FOUNDATION PLAN). CENTERLINE OF EACH PIER MUST BE LOCATED DIRECTLY BELOW THE I-BEAM CENTERLINE.
10. SOIL BEARING CAPACITY SHOWN ON THIS PLAN IS ASSUMED. IF THE ACTUAL SOIL BEARING CAPACITY IS LESS THAN 2,000 PSF, THE ARCHITECT/ENGINEER MUST BE CONSULTED FOR REQUIRED ALTERNATE FOUNDATION DESIGN. FOOTINGS SHALL BE PLACED ON NON-EXPANSIVE SOILS ONLY.
11. INSTALL BLOCK PIER ON EACH SIDE OF ALL EXTERIOR DOOR OPENINGS. (MANUFACTURER'S RECOMMENDATION ONLY - OPTIONAL WHEN NOT SHOWN) SLIGHT ADJUSTMENT MAY BE REQUIRED TO INSURE OPENABILITY AFTER INSTALLATION OF BUILDING IS COMPLETE.
12. THE AREA UNDER FOOTINGS AND FOUNDATIONS SHALL HAVE ALL VEGETATION, STUMPS, ROOTS, AND FOREIGN MATERIALS REMOVED PRIOR TO THEIR CONSTRUCTION.
13. THE FOUNDATION DIMENSIONS SHOWN ARE NOMINAL. AN INCREASE IN MODULE WIDTH SHOULD BE EXPECTED DUE TO MODULE EXPANSION, SETTING TOLERANCES, ETC. THE FOUNDATION CONTRACTOR SHOULD CONSULT WITH THE MANUFACTURER OF THE MODULES PRIOR TO CONSTRUCTION OF THE FOUNDATION TO DETERMINE THE AMOUNT OF INCREASED WIDTH TO BE ADDED TO THE NOMINAL DIMENSIONS SHOWN ABOVE.

NOTE:
EXTERIOR DOORS TO HAVE
PIERS UNDER EACH SIDE

NOTE:
THE NUMBER OF PIERS SHOWN ON THIS FOUNDATION PLAN
IS NO INDICATION OF THE AMOUNT OF PIERS REQUIRED
AND NEEDED FOR THIS BUILDING. SEE MAXIMUM PIER
SPACING CHART TO THE LEFT FOR THE CORRECT NUMBER
OF PIERS REQUIRED FOR EACH SOIL BEARING CAPACITY.







NOTE:
FOUNDATION PIERS AND FOOTING SHOWN ARE FOR
REPRESENTATION ONLY, REFER TO FOUNDATION PLAN
FOR DESIGN DETAILS.

NOTICE TO FOUNDATION CONTRACTOR:
ALL DIMENSIONS, DETAILS, AND NOTES ON THIS FOUNDATION PLAN MUST BE REVIEWED AND VERIFIED BY THE FOUNDATION CONTRACTOR PRIOR TO COMMENCEMENT OF FOUNDATION CONSTRUCTION. ANY APPARENT CONFLICTS, ERRORS, OR OMISSIONS MUST BE BROUGHT TO THE ATTENTION OF THE DESIGN PROFESSIONAL FOR RESOLUTION PRIOR TO PROCEEDING WITH CONSTRUCTION. THE CONTRACTOR MUST OBTAIN APPROVAL OF THE FOUNDATION PLAN FROM THE LOCAL BUILDING DEPARTMENT PRIOR TO COMMENCING CONSTRUCTION AND MUST COMPLY WITH ALL STATE AND LOCAL CODES, APPROVAL, AND INSPECTION REQUIREMENTS. EMC IS NOT THE DESIGNER OF THE BUILDING OR FOUNDATION AND IS NOT RESPONSIBLE OR LIABLE FOR ANY CONFLICTS, OMISSIONS, OR FAILURE TO COMPLY WITH STATE OR LOCAL CODES.

FOUNDATION:
IN ACCORDANCE WITH THE REQUIREMENTS OF THE FLORIDA DEPARTMENT OF BUSINESS AND PROFESSIONAL REGULATION, THESE BUILDING PLANS DO NOT CONTAIN FOUNDATION SUPPORT AND TIE DOWN SYSTEM DETAILS AND SPECIFICATIONS. THE ARCHITECT/ENGINEER OF BUILDING PLANS SHOULD BE CONTACTED TO OBTAIN APPROPRIATE FOUNDATION PLANS. IF FOUNDATION PLANS ARE DESIGNED BY OTHERS, THE ARCHITECT/ENGINEER OF THE BUILDING PLANS SHALL NOT BE HELD RESPONSIBLE OF LIABLE FOR THE FOUNDATION DESIGN AND CONSEQUENTIAL PERFORMANCE OF THE SUPERSTRUCTURE'S STRUCTURAL COMPONENTS AND SYSTEMS RELATING THERETO.

NOTE:
THIS FOUNDATION PLAN IS PROVIDED FOR REFERENCE AS A TYPICAL STANDARD. ACTUAL FOUNDATION CONDITIONS MUST BE EVALUATED FOR APPLICABILITY IF THIS PLAN IS TO BE USED. ALTERNATE FOUNDATION PLANS MAY BE DESIGNED BY OTHERS IN ACCORDANCE WITH THE REQUIREMENTS OF THE JURISDICTION HAVING AUTHORITY.

NOTE:
A SITE SPECIFIC FOUNDATION SHALL BE DESIGNED BY A LICENSED ENGINEER FOR EACH LOCATION THAT THE BUILDING WILL BE INSTALLED. THIS FOUNDATION PLAN IS PROVIDED FOR REFERENCE. MINIMUM REQUIRED SUPPORT LOCATIONS AND MINIMUM GRAVITY LOADS AT THOSE SUPPORT LOCATIONS ARE SPECIFIED ON THIS REFERENCE PLAN. THE ENGINEER OF THE MODULAR BUILDING PLANS SHALL NOT BE HELD RESPONSIBLE OR LIABLE FOR THE FOUNDATION DESIGN AND CONSEQUENTIAL PERFORMANCE OF THE SUPERSTRUCTURE'S STRUCTURAL COMPONENTS AND SYSTEM RELATED THERTO.



WALTER WOOD, P.E.
168 W. LONGLEAF DR.
SYLVESTER, GA 31791

PROJECT HISTORY
START DATE: 2/23/2021

ROSE OFFICE SYSTEMS

TYNDALL AFB

SERIAL No.: SME-20680 A-C

WALTER WOOD, P.E.
CONSULTING ENGINEER
168 W. LONGLEAF DR.
SYLVESTER, GA 31791

PRO MOD
MANUFACTURING
1619 STATE ROAD 26 WEST
ELLAVILLE, GA 31806

DRAWN BY: T. WOOLSEY
CHECKED BY: TEAM
DATE: 2/23/2021
SCALE: N-T-S
EMC# PMM-20680 A-C
SERIAL# 20680 A-C
FOUNDATION SHEET:

1 OF 1